



### Technische Daten

| Typ D   |                 | Typ D mit Dämmgummi   |                        |                  |                 |                       |                              |
|---|-----------------|---|------------------------|------------------|-----------------|-----------------------|------------------------------|
|  |                 |  |                        |                  |                 |                       |                              |
| D (mm)  | Loch<br>Ø (mm)  | Loch Rand-<br>abstand (mm)  | Material<br>b / d (mm) | Lasche<br>a (mm) | Muffe<br>M (mm) | Vorspannmaß<br>V (mm) | mit Dämmgummi<br>Typ x Länge |
| 60  | 11              | 13  | 25 / 3                 | 25               | M10x40          | 3,0                   | 25/8 x 60 (2x)               |
| 64  |                 |   |                        |                  |                 |                       | 25/8 x 70 (2x)               |
| 77  |                 |   |                        |                  |                 |                       | 25/8 x 70 (2x)               |
| 80  |                 |   |                        |                  |                 |                       | 25/8 x 85 (2x)               |
| 84  |                 |   |                        |                  |                 |                       | 25/8 x 85 (2x)               |
| 89  |                 |   |                        |                  |                 |                       | 25/8 x 110 (2x)              |
| 96  |                 |   |                        |                  |                 |                       | 25/8 x 110 (2x)              |
| 100   | 11              | 13  | 30 / 4                 | 30               | M12x40          | 4                     | 25/8 x 130 (2x)              |
| 105   |                 |   |                        |                  |                 |                       | 30/8 x 155 (2x)              |
| 110   |                 |   |                        |                  |                 |                       | 30/8 x 155 (2x)              |
| 116   |                 |   |                        |                  |                 |                       | 30/8 x 155 (2x)              |
| 125   |                 |   |                        |                  |                 |                       | 30/8 x 175 (2x)              |
| 131   |                 |   |                        |                  |                 |                       | 30/8 x 190 (2x)              |
| 137   |                 |   |                        |                  |                 |                       | 30/8 x 190 (2x)              |
| 141   |                 |   |                        |                  |                 |                       | 30/8 x 200 (2x)              |
| 150   |                 |   |                        |                  |                 |                       | 30/8 x 220 (2x)              |
| 157   |                 |   |                        |                  |                 |                       | 30/8 x 220 (2x)              |
| 160   | 13              | 16  | 40 / 4                 | 40               | M16x50          | 4                     | 40/8 x 240 (2x)              |
| 168   |                 |   |                        |                  |                 |                       | 40/8 x 240 (2x)              |
| 176   |                 |   |                        |                  |                 |                       | 40/8 x 260 (2x)              |
| 180   |                 |   |                        |                  |                 |                       | 40/8 x 270 (2x)              |
| 185   |                 |   |                        |                  |                 |                       | 40/8 x 270 (2x)              |
| 200   |                 |   |                        |                  |                 |                       | 40/8 x 295 (2x)              |
| 212   |                 |   |                        |                  |                 |                       | 40/8 x 310 (2x)              |
| 218   |                 |   |                        |                  |                 |                       | 40/8 x 310 (2x)              |
| 225   |                 |   |                        |                  |                 |                       | 40/8 x 345 (2x)              |
| 235   |                 |   |                        |                  |                 |                       | 40/8 x 345 (2x)              |
| 250   | 17              | 25  | 50 / 5                 | 50               | M16x50          | 5                     | 50/8 x 390 (2x)              |
| 267   |                 |   |                        |                  |                 |                       | 50/8 x 405 (2x)              |
| 273   |                 |   |                        |                  |                 |                       | 50/8 x 405 (2x)              |
| 285   |                 |   |                        |                  |                 |                       | 50/8 x 405 (2x)              |
| 315   |                 |   |                        |                  |                 |                       | 50/8 x 425 (2x)              |
| 326   |                 |   |                        |                  |                 |                       | 50/8 x 435 (2x)              |
| 340   |                 |   |                        |                  |                 |                       | 50/8 x 490 (2x)              |
| 355   |                 |   |                        |                  |                 |                       | 50/8 x 530 (2x)              |
| 400   |                 |   |                        |                  |                 |                       | 50/8 x 530 (2x)              |
| 406   |                 |   |                        |                  |                 |                       | 50/8 x 625 (2x)              |
| 429   |                 |   |                        |                  |                 |                       | 50/8 x 625 (2x)              |
| 500   |                 |   |                        |                  |                 |                       | 50/8 x 625 (2x)              |
| 508   |                 |   |                        |                  |                 |                       | 50/8 x 790 (2x)              |
| 532   | 50/8 x 790 (2x) |   |                        |                  |                 |                       |                              |
| 630   | 50/8 x 790 (2x) |   |                        |                  |                 |                       |                              |

D = Außendurchmesser von handelsüblichen Rohren. Rohrschellen sind aus Stahl, feuerverzinkt und Edelstahl 1.4401/1.4571 lieferbar. Technische Änderungen vorbehalten.