


Hammerkopfschrauben

HS 38/17 Stahl galvanisch verzinkt 4.6



Ausführungen: Stahl galvanisch verzinkt, Festigkeitsklasse 4.6

Auslieferung jeweils mit Sechskantmutter DIN 934.

Geeignet für Profil 38/17, 36/36, 38/45 und 36/20.

Abmessung (mm): M10, b = 13,0 / h = 6,0

M12, b = 13,0 / h = 7,0

M16, b = 16,0 / h = 7,0

Gewinde	Länge (mm)	VE (Stück)	Artikelnummer	Preis € / 100 Stück
M 10	20	100	6511.10020	66,50
	30	100	6511.10030	72,10
	40	100	6511.10040	78,10
	50	100	6511.10050	84,15
	60	100	6511.10060	90,10
	70	50	6511.10070	96,10
	80	50	6511.10080	112,55
	100	50	6511.10100	145,50
	150	50	6511.10150	298,50
	200	50	6511.10200	400,30
M 12	20	100	6511.12020	72,35
	30	100	6511.12030	78,85
	40	50	6511.12040	85,55
	50	50	6511.12050	91,90
	60	50	6511.12060	105,20
	70	50	6511.12070	111,60
	80	50	6511.12080	125,20
	100	50	6511.12100	180,45
	125	50	6511.12125	250,35
	150	25	6511.12150	303,25
	200	25	6511.12200	443,65
	250	25	6511.12250	581,35
	300	15	6511.12300	615,00
M 16	30	50	6511.16030	110,40
	40	50	6511.16040	120,75
	50	50	6511.16050	134,85
	60	50	6511.16060	149,30
	80	25	6511.16080	169,70
	100	25	6511.16100	239,10
	125	25	6511.16125	338,25
	150	25	6511.16150	397,30
	200	25	6511.16200	587,00
	300	15	6511.16300	878,05